



Mobil Delvac™ Super 1400E 15W-40

Mobil Commercial Vehicle Lube , Iceland

High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ Super 1400E 15W-40 is a high performance diesel engine oil that provides protection for diesel engines operating under severe service conditions for both on- and off-highway applications. Mobil Delvac Super 1400E 15W-40 is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries

Features and Benefits

- Thermal and oxidation stability Helps to control sludge build-up and deposits
- TBN reserve Helps to control deposits
- Stay-in-grade shear stability Helps to reduce oil consumption and to provide wear protection
- Excellent detergency/ dispersancy Helps to protect and to maintain engines clean
- Component compatibility Long gasket and seal life

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Helps to control sludge build-up and deposits
TBN reserve	Helps to control deposits
Stay-in-grade shear stability	Helps to reduce oil consumption and to provide wear protection
Excellent detergency/ dispersancy	Helps to protect and to maintain engines clean
Component compatibility	Long gasket and seal life

Applications

- Recommended by ExxonMobil for use in:
- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese, and American manufacturers in line with owner manual recommendations

On-highway light and heavy-duty trucking

Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product has the following builder approvals:
MTU Oil Category 1

This product is recommended by ExxonMobil for use in applications requiring:
--

This product is recommended by ExxonMobil for use in applications requiring:

RENAULT TRUCKS RD

RENAULT TRUCKS RD-2

VOLVO VDS-2

ACEA A2

ACEA B2

ACEA E3

API CF

API CF-4

API CG-4

This product meets or exceeds the requirements of:

API SJ

Properties and Specifications

Property	
Grade	SAE 15W-40
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, °C, ASTM D92	230
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.5
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	106
Pour Point, °C, ASTM D97	-27
Total Base Number, mgKOH/g, ASTM D2896	9.7
Viscosity Index, ASTM D2270	140
Specific Gravity, 15 C/15 C, ASTM D4052	0.881
Cold-Cranking Simulator, Apparent Viscosity @ -20 C, mPa.s, ASTM D5293	6150

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2023

17.05.2024

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved