



## Mobil Delvac City Logistics F 5W-30

Mobil Commercial Vehicle Lube , Iceland

Synthetic Light Commercial Vehicle Engine Oil

### Product Description

Mobil Delvac™ City Logistics F 5W-30 is a synthetic engine oil that provides long engine life and excellent engine protection against sludge & wear.

Mobil Delvac™ City Logistics F 5W-30 provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European engines for use in a wide range of light-duty commercial vehicles like Ford but also vans requiring to meet the requirements of ACEA A1/B1 or A5/B5.

### Features and Benefits

Mobil Delvac™ City Logistics F 5W-30 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in recent diesel and gasoline engines as well as older models. Key benefits include:

| Features   | Advantages and Potential Benefits   |
|--|---|
| Increased thermal and oxidation stability  | Help to reduced sludge build-up, deposits, and long oil and engine life         |
| Enhanced wear protection   | Helps towards long component and engine life                                    |
| Advanced piston deposit control  | Helps to keep engines clean with reduced maintenance costs and long engine life |
| Advanced soot handling to control viscosity increase, sludge build up, and filter pressure | Helps to enhance engine protection for long engine life                         |
| Enhanced low temperature pumpability   | Fast start up with reduced wear operating in low temperature climates           |
| Stayed in viscosity grade  | Helps to maintain fuel economy  |

### Applications

ExxonMobil recommends Mobil Delvac™ City Logistics F 5W-30 for demanding driving conditions:

- Ford Light Commercial Vehicles for engines requiring WSS-M2C913-D and also where WSS-M2C913-C is recommended.
- Light Commercial Vehicles requiring ACEA A5/B5 or A1/B1
- Normal to occasionally severe operating conditions (including city driving conditions)

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

|  |
|--|
| <b>This product has the following builder approvals:</b> |
| Ford WSS-M2C913-D  |

**This product meets or exceeds the requirements of:**

ACEA A5/B5

API SL

API SN Engine Test Requirements

Ford WSS-M2C913-C

**Properties and Specifications**

| Property   |           |
|--|-----------|
| Grade  | SAE 5W-30 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 52        |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 9.6       |
| Ash, Sulfated, mass%, ASTM D874                            | 1.08      |
| Total Base Number, mgKOH/g, ASTM D2896                     | 11        |
| Flash Point, °C, ASTM D92                                  | 222       |
| Density @ 15 C, g/ml, ASTM D4052                           | 0.85      |
| Pour Point, °C, ASTM D97                                   | -39       |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023




© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved