



Mobil Super™ 3000 Formula R 5W-30

Mobil Passenger Vehicle Lube , Iceland
Fully Synthetic Engine Oil

Product Description

Mobil Super™ 3000 engine oil series are synthetic and engineered to deliver outstanding protection.

Mobil Super 3000 Formula R 5W-30 is high-performance, low ash engine oil designed to help prolong engine life and maintain the efficiency of the exhaust emission reduction systems in both diesel and gasoline powered passenger cars, light commercial vehicles and vans.

This product is recommended for use in Renault vehicles requiring RN0720 and a wide range of European cars and light-duty commercial vehicles which need to meet or exceed requirements of ACEA C4.

Features and Benefits

- Helps to maintain the efficiency of the exhaust emission reduction systems in both diesel and gasoline vehicles.
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in both gasoline and diesel engine passenger cars, light commercial vehicles and vans.

Applications

ExxonMobil recommends Mobil Super 3000 Formula R 5W-30 for demanding driving conditions:

- Renault passenger cars and light commercial vehicles or vans requiring RN0720
- Passenger cars and light commercial vehicles or vans requiring ACEA C4 for compatibility with GPF or DPF
- Gasoline and Diesel with Diesel Particulate Filters (DPF) and Catalytic Convertors
- Normal to occasionally severe operating conditions (including city driving conditions)

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
RENAULT RN0720
MB-Approval 226.51
This product is recommended for use in applications requiring:
FIAT 9.55535-S4
This product meets or exceeds the requirements of:
ACEA C4

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	73.8
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	12.4
Ash, Sulfated, mass%, ASTM D874	0.5
Phosphorus, mass%, ASTM D4951	0.05
Flash Point, Cleveland Open Cup, °C, ASTM D92	244
Density @ 15 C, g/ml, ASTM D1298	0.85
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved