



Mobil™ Garden Oil 4T

Mobil Passenger Vehicle Lube , Iceland

Engine Oil

Product Description

Mobil™ Garden Oil 4T is a multigrade SAE 10W-30 engine oil designed for 4-stroke garden machines.

Features and Benefits

Mobil Garden Oil 4T 10W-30 combines highly refined, quality mineral oils and balanced additive system to provide following benefits:

- Low oil consumption
- Keeps engine clean
- Protects engine in hot conditions
- Good protection against corrosion

Applications

1. Garden machines with 4-stroke engines, such as lawn mowers, rototillers and chaff cutters.
2. Mobil Garden 4T is also suitable for heavy garden equipment with large high-speed diesel engines.
3. Mobil Garden 4T is ideal for garden equipment that requires SAE 30. It maintains the same viscosity rating of 30 and can also assist with cold starts, providing better protection during cold weather.

The owner's manual should be consulted for the recommended viscosity grade and specification.

Specifications and Approvals

This product is recommended for use in applications requiring:
API SG
API SH
API CF-4
API CF
API SF
API CG-4

This product meets or exceeds the requirements of:
API SJ
API CH-4

This product meets or exceeds the requirements of:

API CI-4

API SL

Properties and Specifications

Property	
Grade	SAE 10W-30
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Viscosity Index, ASTM D2270	141
Pour Point, °C, ASTM D97	-36
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	79.5
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	11.7

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2024




© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved