



Mobil™ Gear Oil FE 75W

Mobil Passenger Vehicle Lube , Iceland

Manual Automotive Transmission Fluid

Product Description

Mobil Gear Oil FE 75W is a high-performance gear oil blended from high quality mineral base oils and an advanced additive system and was specially developed to meet the performance requirements of PSA's (Peugeot / Citroën) manual gearboxes with integrated differentials.

Features and Benefits

Mobil Gear Oil FE 75W is resistant to high temperature and protects from oxidation. Mobil Gear Oil FE 75W provides excellent cold flow and smooth gear shifting and offers the potential for Fuel Efficiency benefits.

Applications

Mobil Gear Oil FE 75W can be used for service fill for all Peugeot & Citroën manual gearboxes fitted into PSA models in Europe.

Specifications and Approvals

This product meets or exceeds the requirements of:

PSA B71 2310

Properties and Specifications

Property	
Grade	SAE 75W
Viscosity Index, ASTM D2270	134
Density @ 15 C, g/ml, ASTM D4052	0.882
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	6.4
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	35
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved