



## Mobil Super™ 3000 X1 Diesel 5W-40

Mobil Passenger Vehicle Lube , Italy

Premium Full Synthetic Passenger Vehicle Diesel Motor Oil

### Product Description

Mobil Super™ 3000 X1 Diesel 5W-40 is a full synthetic motor oil that provides long engine life for many types & ages of vehicles with enhanced protection over a wide temperature range.

### Features and Benefits

Mobil Super 3000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 3000 X1 Diesel 5W-40 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection

### Applications

Mobil Super 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. ExxonMobil recommends Mobil Super 3000 X1 Diesel 5W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- \*Many Diesel engine technologies without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

**This product has the following approvals:**

MB-Approval 229.3

Peugeot/Citroën Automobiles B71 2296

RENAULT RN0710

RENAULT RN0700

VW 502 00

VW 505 00

**This product is recommended for use in applications requiring:**

API CF

GM-LL-B-025

**This product meets or exceeds the requirements of:**

ACEA A3/B3

ACEA A3/B4

**Properties and Specifications**

| Property   |           |
|--|-----------|
| Grade  | SAE 5W-40 |
| Ash, Sulfated, mass%, ASTM D874                            | 1.1       |
| Density @ 15 C, g/ml, ASTM D4052                           | 0.855     |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 222       |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 14        |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 84        |
| Phosphorus, mass%, ASTM D4951                              | 0.0095    |
| Pour Point, °C, ASTM D97                                   | -39       |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2022

**Esso Italiana s.r.l.**

Via Castello della Magliana 25  
00148, Roma, Italia

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.it/it-it/contact-us>

800.011723

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved