



Mobil Delvac™ Super 20W-50

Mobil Commercial Vehicle Lube , Jordan

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Super 20W-50 is high performance diesel engine oil that provides proven engine protection of diesel engines operating in severe service applications. Mobil Delvac Super 20W-50 engine oil is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, construction and agricultural industries.

Features and Benefits

The key benefits of Mobil Delvac Super 20W-50 include:

- Enhanced protection for two and four cycle diesel engines in the most demanding on-and off-highway service
- Prolonged engine life
- Outstanding control of high temperature deposits
- Excellent soot control
- Reduced engine scuffing and bore polishing due to enhanced high temperature/high shear viscosity retention
- Improved low temperature sludge control in stop and- go service
- Easy starting in cold weather conditions
- Extended TBN quality reserve for long term wear and deposit control
- Reduced oil consumption due to improved high temperature performance

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge and build-up of deposits
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Stay-in-grade shear stability	Helps reduce oil consumption and wear

Applications

Mobil Delvac Super 20W-50 is recommended by ExxonMobil for use in the most severe applications of modern on- and off-highway diesel engines. It extends engine life between overhauls in high speed/high load operations and in pickup/delivery operation modes in both two-cycle and four-cycle engines. Applications include:

- Diesel-powered equipment from leading diesel engine manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: trucking, construction, quarrying, and agriculture
- Mixed fleets

Specifications and Approvals

This product is recommended for use in applications requiring:

This product is recommended for use in applications requiring:

API CF

API CF-4

API SF

API SG

Properties and Specifications

Property	
Grade	SAE 20W-50
Density @ 15 C, g/cm ³ , ASTM D4052	0.87
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	163
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	18.2
Cold-Cranking Simulator, Apparent Viscosity @ -15 C, mPa.s, ASTM D5293	6494
Pour Point, °C, ASTM D97	-30
Total Base Number, mgKOH/g, ASTM D2896	6.4
Ash, Sulfated, mass%, ASTM D874	0.72
Flash Point, °C, ASTM D92	231

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2022

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved