



Mobil Super™ High Mileage 0W-20

Mobil Passenger Vehicle Lube , Japan

Fully Synthetic Engine Oil

Product Description

Mobil Super ™ High Mileage 0W-20 is a high performance synthetic oil, which has excellent fuel consumption saving performance and meets the latest fuel economy requirements of ILSAC GF-6A. Formulated with seal conditioner, Mobil Super ™ High Mileage 0W-20 helps prevent leaks and reduce oil consumption.

Features and Benefits

- Excellent fuel consumption saving performance
- Contains seal conditioner to help prevent and control leaks and reduce oil consumption from oil seals and valve systems.
- Prevent sludge and deposit generation, protect your car engine under wide range of driving conditions.
- Low temperature fluidity for smooth start-up, plus exceptional viscosity stability at high operating temperatures.

Applications

Mobil Super ™ High Mileage 0W-20 is recommended for gasoline engine vehicle. It's recommended for cars of the mileage that is beyond 60,000 km.

Specifications and Approvals

| |
|--|
| This product meets or exceeds the requirements of: |
| API SP |
| ILSAC GF-6A |

Properties and Specifications

| Property | |
|---|-----------|
| Grade | SAE 0W-20 |
| Density @ 15 C, g/ml, ASTM D4052 | 0.851 |
| Ash, Sulfated, wt%, ASTM D874 | 1 |
| Total Base Number, mgKOH/g, ASTM D2896 | 9.9 |
| Flash Point, °C, ASTM D92 | 223 |
| Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684 | 20000 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 8.3 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 45 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 2.6 |
| Pour Point, °C, ASTM D97 | -39 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021

ExxonMobil Japan Godo Kaisha

Shinagawa Grand Central Tower

2-16-4, Konan, Minato-Ku,

Tokyo, 108-8218,

Japan

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved