



Mobil Super™ 3000 0W-16

Mobil Passenger Vehicle Lube , Japan

Fully Synthetic Engine Oil

Product Description

Mobil Super™ 3000 0W-16 is a synthetic motor oil, which contributes to the improvement of fuel saving performance while shows excellent engine prot performance.

Features and Benefits

- Helps extend engine life
- Outstanding wear protection for vehicles of all ages
- Excellent high temperature protection
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts
- Meets or exceeds ILSAC GF-6B / API SP.

Applications

Mobil Super™ 3000 0W-16 is a synthetic motor oil, which contributes to the improvement of fuel saving performance while shows excellent engine prot performance.

Specifications and Approvals

This product meets or exceeds the requirements of:	
API SP	
ILSAC GF-6B	

Properties and Specifications

Property	
Grade	SAE 0W-16
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	42000
Viscosity Index, ASTM D2270	163
Total Base Number, mgKOH/g, ASTM D2896	7.4
Pour Point, °C, ASTM D97	-42

Property	
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	36
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	7
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.3
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Density @ 15 C, g/ml, ASTM D1298	0.845
Ash, Sulfated, mass%, ASTM D874	0.7

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023
ExxonMobil Japan Godo Kaisha
Shinagawa Grand Central Tower
2-16-4, Konan, Minato-Ku,
Tokyo, 108-8218,
Japan

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTOMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved