



## Mobil Special™ 10W-30

Mobil Passenger Vehicle Lube , Japan

High Performance Motor Oils

### Product Description

Mobil Special™ 10W-30 is high performance gasoline engine oils that deliver engine protection and cleanliness.

### Features and Benefits

- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Multigrade motor oils allowing easier starts at low temperatures
- Good high temperature properties

### Applications

Mobil Special 10W-30 is recommended for use in a wide range of applications and operating conditions.

### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
API CF

<b>This product meets or exceeds the requirements of:</b>
API SN

### Properties and Specifications

Property	
Grade	SAE 10W-30
Viscosity Index, ASTM D2270	139
Density @ 15 C, g/ml, ASTM D4052	0.87
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Ash, Sulfated, mass%, ASTM D874	0.9
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	67

Property	
Pour Point, °C, ASTM D97	-31
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	17700
Total Base Number, mgKOH/g, ASTM D2896	8.3

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

EMG Lubricants Godo Kaisha

Lubricants Customer Response Center

Yokohama Blue Avenue, 4-4-2 Minatomirai, Nishi-Ku, Yokohama-city

Kanagawa 220-0012

Japan

Tel : 0120-016-313 (only from Japan local)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved