



Mobil Super™ All-In-One Protection X1 5W-40

Mobil Passenger Vehicle Lube , Japan

Full Synthetic Engine Oil

Product Description

Mobil Super™ All-In-One Protection X1 5W-40 is a premium full synthetic engine oil, designed to provide outstanding levels of protection for modern vehicles in city driving.

Features and Benefits

Mobil Super™ All-In-One Protection X1 5W-40 is industry proven so you can enjoy the freedom and convenience of driving with engine well protected from harsh conditions of city driving.

Mobil Super All In One Protection X1 5W-40

provides:

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

Applications

Mobil Super™ All-In-One Protection X1 5W-40 is formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend this product if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- Turbo Chargers and Direct Injection engines
- High Performance Engines

Specifications and Approvals

This product has the following approvals:
BMW Longlife 01
MB-Approval 229.3
MB-Approval 229.5
VW 502 00

This product has the following approvals:

VW 505 00

This product is recommended for use in applications requiring:

API CF

This product meets or exceeds the requirements of:

API SP

Properties and Specifications

Property	
Grade	SAE 5W-40
Pour Point, °C, ASTM D97	-39
Total Base Number, mgKOH/g, ASTM D2896	12.5
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	78
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁶ sec ⁻¹ , mPa.s, ASTM D4683	3.7
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.1
Density @ 15.6 C, g/ml, ASTM D4052	0.847
Viscosity Index, ASTM D2270	169

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2022

ExxonMobil Japan Godo Kaisha

Shinagawa Grand Central Tower

2-16-4, Konan, Minato-Ku,

Tokyo, 108-8218,

Japan


Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit

www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved