



Mobil 1™ ESP 5W-30

Mobil Passenger Vehicle Lube , Kenya

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1™ ESP 5W-30 advanced performance synthetic engine oil is a select member of Mobil 1™, the world's leading synthetic engine oil brand delivering our ul performance and protection. Mobil 1™ ESP 5W-30 is engineered to deliver excellent all-round protection for Euro 6 and prior gasoline and diesel powered autom and meets or exceeds the requirements of many leading car manufacturers.

Mobil 1 keeps your engine running like new!

Features and Benefits

Mobil 1 ESP 5W-30 is made with a proprietary blend of leading edge components formulated to help provide exceptional cleaning power and wear protection, i fully compatible with the Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's).

Features	Advantages and Potential Benefits
Low Ash content	Helps to reduce particulate build-up in Diesel Particulate Filters
Low Sulphur and Phosphorous content	Helps to reduce poisoning of Gasoline Catalytic Converters
Active cleaning agents	Helps to reduce deposits and sludge build-up to enable clean and long engine life
Excellent thermal and oxidative stability	Helps to reduce oil aging allowing extended drain interval protection
Excellent low temperature capabilities	Quick cold weather starting and fast protection to help extend engine life
Meets industry latest LSPI requirements for gasoline direct injection turbocharged engines	Helps prevent engine breakdown resulting from pre-ignition occurrences at engine low s and high torque operation

Applications

Mobil 1 ESP 5W-30 carries recommendations for a wide range of passenger cars, SUVs and light vans. It is designed for modern high efficiency gasoline, dies hybrid cars from Porsche, BMW, Volkswagen, Opel and Mercedes-Benz as well as for Japanese and Korean vehicles that specifically call for a SAE 5W-30 viscosity and any of the specifications the oil supports, allowing for extended oil change intervals where recommended by the manufacturer.

- Mobil 1 ESP 5W-30 is a low ash (mid SAPS) engine oil to help protect exhaust gas after-treatment systems designed to limit engine emissions. It fully meets or e: ACEA C3 industry standard and is suitable for the operation and protection of engines and after-treatment systems of vehicles calling for ACEA C2. However provides the fuel economy potential required by the C3 and not the C2 classification.
- Mobil 1 ESP 5W-30 meets or exceeds the requirements of 'API SP' industry standard therefore helping address LSPI (Low Speed Pre-Ignition) and making it a pre choice for modern downsized direct injection turbocharged gasoline engines.
- Mobil 1 ESP 5W-30 is especially suitable for extreme conditions where conventional oil often may not perform.
- Mobil 1 ESP 5W-30 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Owner's manual should be consulted for recommended viscosity grade and specification.

Specifications and Approvals

This product has the following approvals:	
BMW Longlife 04	
MB-Approval 229.31	
MB-Approval 229.51	
MB-Approval 229.52	
OV 040 1547 – D30	
OV 040 1547 – G30	
Porsche C30	
VW 504 00	
VW 507 00	

This product is recommended for use in applications requiring:	
FIAT 9.55535-S3	
Recommended by ExxonMobil for applications requiring ACEA C2	

This product meets or exceeds the requirements of:	
API SJ	
API SL	
API SM	
API SN	
API SN PLUS	
API SP	
ACEA C3	

Properties and Specifications

Property	
Grade	SAE 5W-30
Pour Point, °C, ASTM D97	-42
Ash, Sulfated, mass%, ASTM D874	0.8
Flash Point, Cleveland Open Cup, °C, ASTM D92	234

Property	
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	67
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.5
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.9
Density @ 15.6 C, g/ml, ASTM D4052	0.851
Viscosity Index, ASTM D2270	175

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024
Mobil Oil Kenya Ltd.
P.O. Box 64900 - 00620, Nairobi

+ 254 2 3767842-9

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro
performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc
All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende
override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTOMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved