



Mobil 1™ FS X2 5W-40

Mobil Passenger Vehicle Lube , Cambodia

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ FS X2 5W-40 European Car Formula is an advanced full synthetic motor oil engineered for the latest gasoline and diesel (without DPFs) engine technology delivering excellent all-around performance. It provides exceptional cleaning power, wear protection and overall performance.

Features and Benefits

Mobil 1 FS X2 5W-40 is made with a proprietary blend of ultra-high performance synthetic basestocks fortified with a precisely balanced component system.

Features	Advantages and Potential Benefits
Outstanding thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Excellent low temperature capabilities	Outstanding cold starting and fast lubrication to protect against wear
Active cleaning agents	Designed to clean up sludge left behind in your engine
Low oil volatility	Helps reduce oil consumption
High viscosity index	Excellent overall lubrication and wear protection performance for many driving styles and conditions, from mild to severe

Applications

Mobil 1 FS X2 5W-40 is recommended by ExxonMobil for all types of vehicles, including high-performance turbo-charged, supercharged gasoline and certain multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.

- Mobil 1 FS X2 5W-40 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

Specifications and Approvals

This product has the following approvals:
MB-Approval 229.3
Porsche A40
VW 502 00
VW 505 00

This product is recommended for use in applications requiring:
API CF

This product meets or exceeds the requirements of:
API SN
ACEA A3/B3
ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 5W-40
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.6
Total Base Number, mgKOH/g, ASTM D2896	12.6
Pour Point, °C, ASTM D97	-45
Density @ 15 C, g/cm3, ASTM D4052	0.849
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	80
Ash, Sulfated, mass%, ASTM D874	1.3
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.8
Flash Point, Cleveland Open Cup, °C, ASTM D92	227
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	17000

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022

ExxonMobil

Exxon

Mobil

ESSO

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved