



## Mobil Outboard™ Plus

Mobil Passenger Vehicle Lube , Cambodia

Superior Performance Two-Stroke Outboard Engine Oil

### Product Description

Mobil Outboard Plus is a high performance, two-stroke engine oil that is designed for many high performance, water-cooled two-stroke engines used in outboard marine applications. Mobil Outboard Plus offers clean engine and environmental performance. Mobil Outboard Plus is pre-diluted to facilitate mixing when added to fuel.

### Features and Benefits

Mobil Outboard Plus is formulated from high purified conventional mineral oils and an ashless dispersant additive system providing outstanding protection against exhaust port deposits, corrosion and wear. Spark plug fouling and pre-ignition are also minimised promoting flawless operation. The product is ideal for use in both modern and older two stroke engine models. Key features and benefits include:

| Features  | Advantages and Potential Benefits   |
|---|---|
| Good thermal and oxidation stability and deposit control            | Cleaner engines resulting in reduced ring sticking and cylinder scuffing, extended engine life and more reliable operation                      |
| Outstanding anti-wear protection                                    | Extended life of critical components and engine   |
| Excellent corrosion protection properties                           | Longer engine life  |
| Promotes cleaner combustion and reduced deposits in combustion area | Reduces plug fouling and exhaust port deposits thus minimising pre-ignition, extending spark plug and valve life and increasing fuel efficiency |
| Good high and low temperature capability                            | Wide range of ambient temperature application   |
| Non-toxic to marine life  | No lingering side affects to marine life  |

### Applications

Mobil Outboard Plus is recommended by ExxonMobil for use in modern high-performance, water-cooled, two-stroke engines, as well as, smaller or older outboard engines. ExxonMobil also recommend Mobil Outboard Plus for use in two-stroke engines manufactured by Johnson, Mercury, OMC, Evinrude, Mariner, Force, Mercruiser, Yamaha, Suzuki, Nissan and Tohatsu or where NMMA TC-W, TC-WII or TC-W3 oils are recommended.

ExxonMobil also recommend Mobil Outboard Plus for use in light to moderate duty, air-cooled two-stroke engines that are used in power mowers, chain saws, leaf blowers and lawn trimmers.

### Specifications and Approvals

|   |
|---|
| <b>This product meets or exceeds the requirements of:</b> |
| API TC  |

### Properties and Specifications

| Property   |      |
|--|------|
| Color, Visual  | Blue |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 8.8  |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 52.9 |
| Pour Point, °C, ASTM D97                                   | -36  |
| Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93       | 100  |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved