



Mobil Delvac™ MX Advanced City Logistics 5W-40

Mobil Commercial Vehicle Lube , South Korea

Description

Mobil Delvac™ MX Advanced City Logistics 5W-40 is formulated to deliver high performance in commercial diesel engines equipped with a Diesel Particulate Filter and is suitable for driving conditions of city logistics applications. Mobil Delvac™ MX Advanced City Logistics 5W-40 provides protection for DPFs and diesel e under the conditions of frequent start-ups, stop and go driving in urban areas, and powerful driving for heavy loaded light commercial vehicles.

Features and Benefits

- Helps to maintain the efficiency of the Exhaust Emission Reduction systems in commercial vehicles.
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in diesel engine light commercial vehicles.

Application

- Mobil Delvac™ MX Advanced City Logistics 5W-40 has been developed to meet the latest specifications for engine oils required by major car manufacturers compatible with most latest Diesel Particulate Filters
- Mobil Delvac™ MX Advanced City Logistics 5W-40 offers excellent performance at both very low and very high operating temperatures and long term protection from wear and sludge and deposit build-up.

Specification

Mobil Delvac™ MX Advanced City Logistics 5W-40 meets or exceeds the requirements of:
ACEA C3

Typical Properties

Mobil Delvac™ MX Advanced City Logistics 5W-40	
Viscosity, ASTM D 445	
cSt @ 40° C	74.9
cSt @ 100° C	12.8
Sulfated Ash, wt%, ASTM D 874	0.8
Phosphorous, wt%, ASTM D 4951	0.08
Flash Point, °C, ASTM D 92	230
Density @15° C kg/l, ASTM D 4052	0.852
Pour Point, °C, ASTM D 97	-33

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2021

Mobil Korea Lube Oil Inc.

Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea

+82-2-750-8700

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

ATOMOBILE

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved