



## Mobil Delvac 1330

Mobil Commercial Vehicle Lube , South Korea

Heavy Duty Diesel Engine Oils

### Product Description

Mobil Delvac 1330 is high performance, heavy duty diesel engine oil formulated from advanced technology base oils and a balanced additive system. It is specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off highway conditions. Mobil Delvac 1330 is used in a wide range of applications where a monograde lubricant is recommended.

### Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life, Less wear, Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control

### Applications

- Naturally aspirated and turbo-charged diesel powered equipment
- On highway light and heavy duty trucking
- Off highway industries including: construction, mining, quarrying, and agriculture

### Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:
Allison C-4
API CF
API SF

### Properties and Specifications

Property	
Grade	SAE 30
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.8
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	84.8
Density @ 15.6 C, g/ml, ASTM D4052	0.879
Pour Point, °C, ASTM D97	-24

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	240
Ash, Sulfated, mass%, ASTM D874	1.2
Total Base Number, mgKOH/g, ASTM D2896	10

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

Mobil Korea Lube Oil Inc.

Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea

+82-2-750-8700

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved