



Mobil Vacuoline™ 500 Series

Mobil Industrial , South Korea

Circulating Oils

Product Description

The Mobil Vacuoline 500 Series family of products provides a versatile lubricant source for a wide range of industrial equipment. The Mobil Vacuoline 500 Series lubricants are high performance heavy duty circulating oils designed for the demands of No-Twist Rod mills, however their all round performance makes them a excellent choice for circulation systems lubricating gears and bearings. Mobil Vacuoline 500 Series are designed to meet the critical requirements of the Morgan Construction Company's high speed No-Twist Rod Mills, as well as the circulation oil requirements of Danielli rod mills.

They are formulated from high quality base stocks and a proprietary additive system to provide superior wettability, extra oil retention and thin film protection against rust and corrosion. Mobil Vacuoline 500 gives excellent resistance to oxidation and thermal degradation, and a high level of protection against wear. They possess excellent demulsibility that permits water and other contaminants to separate readily from the oil in the system reservoir. The Mobil Vacuoline 500 Series are available in a variety of viscosity grades.

Features and Benefits

The Mobil Vacuoline 500 Series family of products is well known and highly regarded world-wide based on their outstanding performance and the Research and Development expertise and global technical support which stand behind the brand. The highly versatile performance of Mobil Vacuoline 500 Series oils, has made them the choice of many users around the world for many decades.

Mobil Vacuoline 500 series are designed for lubrication of circulation systems of No-Twist Rod Mills, industrial and marine gearboxes, hydraulic systems plus a wide variety of ancillary equipment.

Features	Advantages and Potential Benefits
Good protection against rust and corrosion through a balanced high performance lubricant formulation	Fewer unscheduled stoppages and lower maintenance costs
Outstanding antiwear performance	Excellent protection of critical bearings and gears
Excellent water separation characteristics	Rapid separation of water for smooth, efficient operation, reduced downtime and undiminished wear protection
High resistance to oxidation and thermal degradation	Long oil change life and avoidance of costs of unanticipated production interruption
Multiple application capability	Inventory Savings

Specifications and Approvals

This product has the following approvals:	525
Danielli Type 21-0.597654.F BGV No Twist Stand Block-TMB/TFS Rev 15	X

This product meets or exceeds the requirements of:	525
Morgan No-Twist® Mill Oil Quality Specification	X

Properties and Specifications

Property	525	528	533	537	546	548
Grade	ISO 100	ISO 150	ISO 220	ISO 320	ISO 460	ISO 68
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1A	1A	1A	1A	1A	1A
Demulsibility, Total Free Water, Non-EP Oils, ml, ASTM D2711	39	38	36	39	35	36
Density @ 15 C, kg/l, ASTM D1298	0.88	0.89	0.89	0.89	0.9	0.92
Emulsion, Time to 37 mL Water, 54 C, min, ASTM D1401	15					
Emulsion, Time to 37 mL Water, 82 C, min, ASTM D1401		15	15	15	15	15
Emulsion, Time to 40/37/3, 82 C, min, ASTM D1401		10	15	20	25	
FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1	12	12	12	12	12	12
Flash Point, Cleveland Open Cup, °C, ASTM D92	264	272	284	288	286	286
Foam, Sequence I, Stability, ml, ASTM D892	0	0	0	0	0	0
Foam, Sequence I, Tendency, ml, ASTM D892	10	5	5	10	5	0
Foam, Sequence II, Stability, ml, ASTM D892	0	0	0	0	0	0
Foam, Sequence II, Tendency, ml, ASTM D892	0	0	0	0	0	0
Foam, Sequence III, Stability, ml, ASTM D892	0	0	0	0	0	0
Foam, Sequence III, Tendency, ml, ASTM D892	0	0	0	0	0	0
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.7	14.4	18.8	24.4	29.4	36.9
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	92.7	146	215	309	453	677
Pour Point, °C, ASTM D97	-24	-21	-15	-12	-12	-9
Rust Characteristics, Procedure A, ASTM D665	PASS	PASS	PASS	PASS	PASS	PASS
Rust Characteristics, Procedure B, ASTM D665	PASS	PASS	PASS	PASS	PASS	PASS
Viscosity Index, ASTM D2270	99	96	96	96	95	89

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2024

Mobil Korea Lube Oil Inc.

Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea

+82-2-750-8700

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved