



Nyvac™ FR 200D

Mobil Industrial , South Korea

High Performance Fire-resistant Hydraulic Fluid

Product Description

Mobil Nyvac FR 200D is an extra high performance water-glycol type fire-resistant hydraulic fluid. It is formulated with diethylene glycol as the main glycol comp The product does not contain ethylene glycol. Mobil Nyvac FR 200D provides excellent protection against rust and against vapour phase corrosion. In hydraulic tests, it has shown a high level of antiwear performance. A high viscosity index makes Mobil Nyvac FR 200D effective over a wide range of operating temperatu foam resistance, low temperature flow and storage stability are also excellent.

The fire-resistant properties of Mobil Nyvac FR200D arise from its water content. Even when the fluid is sprayed at a pressure of over 200 bar / 3000 psi from a injector nozzle into a gas flame it will not ignite, nor will it when dropped onto molten metal. The water content is important and must be maintained at 38% to optimum fire resistant properties and its viscosity characteristics. Viscosity increase due to loss of water by evaporation can be easily corrected by adding deionised to the product. It is not recommended for use in systems operating at bulk fluid temperatures above 65° C. Mobil Nyvac FR 200D is compatible with packings, g hoses and accumulators made from materials normally encountered in hydraulic systems, except items made from polyurethane, leather or cork materials. Mobil FR 200D is approved by FM Global.

Mobil Nyvac FR 200D's wide application capability and excellent performance make it the product of choice among many industrial users.

Features and Benefits

Mobil Nyvac FR 200D is a key member of the Mobil brand of fire-resistant hydraulic fluids. Mobil Nyvac FR 200D was developed in conjunction with hydraulic equi builders to meet the needs of moderate pressure applications where fire-resistance properties are critical, and where good lubricity and product life are also require

| Features                                     | Advantages and Potential Benefits                                                                    |
|----------------------------------------------|------------------------------------------------------------------------------------------------------|
| Outstanding fire-resistant properties        | Safer working conditions for people and plant                                                        |
| Excellent lubricity and antiwear properties  | Minimum pump and valve wear when used in accordance with the equipment manufacturer's recommendation |
| High viscosity index                         | Wide range of applications for reduced inventory costs                                               |
| Very good low temperature fluidity           | Good cold-start performance                                                                          |
| Very good lubricity and antiwear performance | Pump and valve protection and long life and reduced replacement part costs                           |
| Excellent storage stability                  | Easy handling in the plant and reduced waste                                                         |

Applications

In common with all other water-glycol type fluids, Mobil Nyvac FR 200D is not compatible with typical type paints. Epoxy or phenolic resin based paints are su Mobil Nyvac FR 200D should not be mixed with other types of fluids. While it is compatible with other water-glycol type products, admixtures may detract frc properties of the Mobil product. The water content is important and must be maintained at 38% to retain optimum fire resistant properties and its viscosity characte It is not recommended for use in systems operating at bulk fluid temperatures above 65° C.

Mobil Nyvac FR 200D is recommended for use in all types of hydraulic pumps and motors operating close to a source of ignition, providing the manufacturers instr are observed. Typical applications include:

- Diecasting machines and presses
- Combustion regulators
- Furnace door openers
- Ladel-tilting mechanisms

- Glass drawing machinery

Specifications and Approvals

|                                           |
|-------------------------------------------|
| This product has the following approvals: |
| FM Global Approvals Class 6930            |

Properties and Specifications

| Property                                     |       |
|----------------------------------------------|-------|
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 41.5  |
| pH, AM-S 1436                                | 9.5   |
| Pour Point, °F, ASTM D97                     | -30   |
| Specific Gravity, 15.6 C/15.6 C, ASTM D1298  | 1.089 |
| Viscosity Index, ASTM D2270                  | 175   |
| Water, wt %, ASTM E203                       | 43    |
| Color, Visual                                | Red   |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024  
Mobil Korea Lube Oil Inc.  
Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea  
+82-2-750-8700

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTOMOBILE

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved