



## Mobil Super 1000 XE Diesel 5W-30

Mobil Passenger Vehicle Lube , South Korea

Premium Multigrade Passenger Vehicle Engine Oils

### Product Description

Mobil Super™ 1000 XE Diesel 5W-30 is a quality premium mineral motor oil designed to provide a high level of performance and protection under most operating conditions. It is a low ash engine oil designed to help prolong the life and maintain the efficiency of the Exhaust Car Emission Reduction Systems in diesel powered automobiles

### Features and Benefits

Mobil Super 1000 XE Diesel 5W-30 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and extends engine life.

- Excellent wear protection
- Excellent engine cleanliness

### Applications

Mobil Super 1000 XE Diesel 5W-30 is suitable for use in diesel powered vehicles. It is ideally suited for less stressful driving conditions such as highway driving and lower consistent speed conditions.

### Specifications and Approvals

Mobil Super 1000 XE Diesel meets or exceeds the requirements of:	5W-30
API SN	X
ACEA C3	X

### Typical Properties

Mobil Super 1000	
SAE Grade	5W-30
Viscosity, ASTM D 445	
cSt @ 40°C	67.7
cSt @ 100°C	11.6
Viscosity Index, ASTM D 2270	168
Sulfated Ash, wt%, ASTM D 874	0.8
HTHS Viscosity, mPa·s @ 150°C, ASTM D4683	3.5
Pour Point, °C, ASTM D 97	-39
Flash Point, °C, ASTM D 92	237
Density @ 15 °C, kg/l, ASTM D4052	0.85

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil, Mobil 1, the 1 Icon, and Mobil Super are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries. dexos1™ is a registered trademark of General Motors LLC.

11-2020

Mobil Korea Lube Oil Inc.

Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea

+82-2-750-8700

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved