



Mobil Super™ 2000 5W-20

Mobil Passenger Vehicle Lube , South Korea

Semi Synthetic Engine Oil

Product Description

Mobil Super™ 2000 5W-20 is a premium semi-synthetic engine oil, designed to provide reliable protection to modern engines.

Features and Benefits

Mobil Super 2000 5W-20 is industry proven so you can be assured of reliable protection for your vehicle. Mobil Super™ 2000 5W-20 contains low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy:

- Excellent wear protection
- Excellent engine cleanliness
- Excellent high temperature protection
- Enhanced fuel economy from lower viscosity

Applications

Mobil Super 2000 5W-20 is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest gasoline engines
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal to occasionally severe operating conditions
- Turbo-Chargers
- Stop and Go City Driving

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:
Ford WSS-M2C930-A
GM 6094M

This product meets or exceeds the requirements of:
API SJ
API SL
API SM

This product meets or exceeds the requirements of:
API SN
API SN PLUS
API SN PLUS RESOURCE CONSERVING
API SN Resource Conserving
Ford WSS-M2C945-A
Ford WSS-M2C945-B1

Properties and Specifications

Property	
Grade	SAE 5W-20
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	49
Viscosity Index, ASTM D2270	146
Density @ 15.6 C, g/ml, ASTM D4052	0.859
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	216
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	7.5
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	14900
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

Mobil Korea Lube Oil Inc.

Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea

+82-2-750-8700


Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local

ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved