



## Mobil Delvac Legend™ Commercial Vehicle 10W- 30

Mobil Commercial Vehicle Lube , Kazakhstan

Multigrade Light Duty Diesel Engine Oil

### Product Description

Mobil Delvac Legend commercial Vehicle 10W-30 is Multigrade light Duty diesel engine oil specifically engineered to provide excellent lubrication of diesel engines operating in severe conditions. This diesel engine oil is designed using a blend of high performance synthetic blend base oils to provide excellent low temperature fluidity, high temperature viscosity retention, and volatility control. These base oils are enhanced with an advanced additive system, which provides a high level of protection to all parts of the engine.

### Features and Benefits

The technology in Mobil Delvac Legend commercial Vehicle 10W-30 delivers strong performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Good protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Helps to control of high temperature deposits Helps to reduce wear and to provide long engine life Protection against ring sticking
Excellent low temperature properties	Ready oil "pumpability" / circulation Start-up wear protection
Stay-in-grade shear stability	Viscosity maintenance and reduced oil consumption under heavy-duty, high temperature operating conditions

### Applications

Recommended by ExxonMobil for use in:

- Recommended for use in turbo-charged, low emission diesel engines of European and American design
- On highway applications operating in both high speed/high load and short haul pick-up/delivery in light and heavy-duty trucking

### Specifications and Approvals

This product is recommended for use in applications requiring:
API CF
API CF-4
API CG-4
API SH
VOLVO VDS-2

**This product is recommended for use in applications requiring:**

API SF

API SG

**This product meets or exceeds the requirements of:**

API CH-4

API SJ

**Properties and Specifications**

Property	
Grade	SAE 10W-30
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	11.7
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	80
Pour Point, °C, ASTM D97	-36
Total Base Number, mgKOH/g, ASTM D2896	8.9
Viscosity Index, ASTM D2270	141
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Density @ 15 C, kg/l, ASTM D4052	0.87
Ash, Sulfated, mass%, ASTM D874	1.1

**Health and safety**


Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved