



Mobil SHC Chain 240

Mobil Industrial , Kazakhstan

High Temperature Chain Lubricant

Product Description

Mobil SHC Chain 240 is an exceptional performance chain lubricant designed for lubrication of high temperature conveyor chains at temperatures up to 290°C / 555°F. It is designed to provide excellent wear protection and resistance to evaporation, thermo-oxidation and coking.

Features and Benefits

Mobil SHC Chain 240 helps to:

- Provide a degree of equipment protection beyond the capabilities of conventional chain lubricants
- Provide extra reassurance of trouble-free equipment protection at very high temperatures
- Extend equipment life, reduce costs, improve total system performance
- Prevent wear of chains, sprockets, and other system components
- Reduce deposit formation thereby reducing chain sticking
- Provide lasting lubrication of chains at high temperatures
- Reduce lubricant consumption compared to conventional chain lubricants

Applications

Mobil SHC Chain 240 is designed specifically for the lubrication of oven conveyor chains at temperatures up to 290°C (555° F). It is suitable for high temperature chain applications in:

- Fiber glass insulation manufacture
- Particleboard (OSB , MSB) manufacture
- Plastics and textiles manufacture
- Paint oven operations

Typical Properties

Test	Mobil SHC Chain 240
Density, kg/dm ³ , ISO 12185	0.968
Kinematic Viscosity, mm ² /s, ISO 3104	
- @ 40°C	245
- @ 100°C	19
Viscosity Index, ISO 2909	86
Flash Point, COC, °C, ISO 2592	290
Pour Point, °C, ISO 3016	-24
Foam, ISO 6248	
-Seq I, Tendency, ml	50
-Seq I, Stability, ml	0
Evaporative Loss, wt%, 204°C, 6.5 hrs, ASTM D972	1%

Test	Mobil SHC Chain 240
Copper Corrosion, 100°C, 3 hrs, ASTM D130	1A
4-Ball Wear, wear scar, mm, ASTM D4172	0.4
4-Ball Weld Load, kg, ASTM D2783	160

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved