



Mobilube™ GX 80W-90

Mobil Commercial Vehicle Lube , Laos

Heavy Duty Automotive Gear Lubricants

Product Description

Mobilube GX 80W-90 is high performance, heavy duty gear lubricants formulated from high quality base oils and an advanced additive system. This lubricant is engineered for automotive heavy-duty transmissions, axles, and final drives where protection against wear and scoring is required. It is recommended by ExxonMobil for use in applications where API GL-4 service is required.

Features and Benefits

Today's heavy equipment applications place higher performance demands on drivetrain lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and optimise operating costs. Longer service intervals place additional demands on the gear lubricant requiring effective basestock and additive systems. Mobilube GX 80W-90 is engineered to meet these challenges. The key benefits include:

Features	Advantages and Potential Benefits
Good thermal stability and resistance to high temperature oxidation.	Extended gear and bearing life due to minimal deposits. Longer seal life.
Excellent rust and corrosion protection.	Longer component life.
Good low temperature lubrication.	Reduced wear at start-up and ease of start-up.
Compatible with typical seals and gaskets.	Minimum leakage and reduced contamination.

Applications

Recommended by ExxonMobil for use in:

- Heavy duty manual transmissions, axles and final drives requiring API GL-4 level performance.
- Passenger cars, on highway light and heavy duty trucks, and commercial vehicles.
- Off highway industries including: construction, mining, quarrying, and agriculture.
- Other heavy duty industrial and automotive applications including hypoid gears operating under moderate to severe conditions.

Specifications and Approvals

This product is recommended for use in applications requiring:
API GL-4

Properties and Specifications

Property	
Grade	SAE 80W-90

Property	
Viscosity Index, ASTM D2270	97
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	143
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.2
Flash Point, °C, ASTM D92	244
Density @ 15 C, g/ml, ASTM D4052	0.88

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2022

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved