



## Mobil™ ATF 220 Syn Tech

Mobil Passenger Vehicle Lube , Laos

Automatic Transmission Fluid

### Product Description

Mobil™ ATF 220 Syn Tech is a high performance fluid for automatic transmissions in vehicles requiring Dexron II/IIID. It is also used as a hydraulic fluid in unique applications.

### Features and Benefits

Mobil ATF 220 Syn Tech is formulated from high-quality conventional base oils combined with a special additive system including viscosity index improvers, antioxidants, and defoamers providing smooth and controlled friction/wear characteristics. The product provides consumers an excellent driving experience even in broad range of driving conditions in a wide variety of automobiles requiring Dexron II/IIID specifications.

Features	Advantages and Potential Benefits
Good thermal and oxidation stability	Resists lacquer, sludge and deposit formation to keeps transmissions clean for efficient operation over the fill life
Good anti-wear properties	Meets the wear requirement to promote longer transmission life
Excellent low-temperature fluidity	Assist in improved start-up and clean fast lubrication at low ambient temperatures
Effective foam control properties	Smooth and lasting shift feel and reduced fluid loss in severe service-operating conditions
Compatible with all common seal materials used in Type IID transmissions	Maintains effective leakage control

### Applications

Mobil ATF 220 Syn Tech is recommended for some automatic and manual transmissions in passenger cars and light trucks specifying Dexron II/IIID level performance as well as the related power steering systems. It is also suitable for use in some special hydraulic systems in farm equipment and other installations having similar fluid requirements. It is recommended that the user consult the manufacturer's requirements. Other applications include:

- Off-highway transmissions power steering and other hydraulic systems.
- Industrial hydraulic systems and components.

### Specifications and Approvals

This product is recommended for use in applications requiring:
Ford ESR-M2C163-A2
GM DEXRON II
GM DEXRON IID

**This product is recommended for use in applications requiring:**

GM Type A Suffix A

MB 236.7

R. Bosch AS TE-ML 09

**Properties and Specifications**

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	229
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	40.5
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	7
Pour Point, °C, ASTM D97	-42
Color, Visual	Red
Density @ 15 C, g/cm <sup>3</sup> , ASTM D4052	0.8624
Viscosity Index, ASTM D2270	131
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	41200

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023




© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved