Mobil

Mobil Delvac Legend™ 15W-40 Complete Defense

Mobil Commercial Vehicle Lube , Sri Lanka

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Legend[™] 15W-40 Complete Defense is a high performance diesel engine oil that provides proven engine protection of diesel engines operating in c off-highway severe service applications.

Mobil Delvac Legend 15W-40 Complete Defense is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments in the trucking, mining, construction, quarrying, and agricultural industries.

This product is fully compatible with Mobil Delvac Super 1300 15W-40 and can be used as a replacement of same.

Features and Benefits

The technology in Mobil Delvac Legend 15W-40 Complete Defense delivers excellent performance in both modern diesel engines as well as older models. The benefits include:

| Features | Advantages and Potential Benefits |
|----------------------------------|---|
| Thermal and oxidation stability | Controls sludge build-up and deposits |
| TBN reserve | Deposit control |
| Stay-in-grade shear stability | Reduced oil consumption and wear protection |
| Excellent detergency/dispersancy | Cleaner engines and longer engine life |
| Component compatibility | Longer gasket and seal life |

Specifications and Approvals

| This product is recommended for use in applications requiring: |
|--|
| ACEA E2 |
| API CF-4 |
| API CG-4 |
| MB 228.1 |
| VOLVO VDS |
| |

This product meets or exceeds the requirements of:

API SJ

Properties and Specifications

| Property | |
|---|------------|
| Grade | SAE 15W-40 |
| Viscosity Index, ASTM D2270 | 136 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 106 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 14.2 |
| Flash Point, °C, ASTM D92 | 220 |
| Density @ 15 C, kg/l, ASTM D4052 | 0.88 |
| Total Base Number, mgKOH/g, ASTM D2896 | 9 |
| Pour Point, °C, ASTM D97 | -27 |
| Ash, Sulfated, mass%, ASTM D874 | 1.0 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

