



## Mobil Super Moto™ 20W-40

Mobil Passenger Vehicle Lube , Sri Lanka

Premium Four-Stroke Motorcycle Engine Oil

### Product Description

Mobil Super Moto™ 20W-40 is high performance engine oil for modern motorcycle engines. Though developed for latest engine technology, Mobil Super Moto 20W-40 provides good protection for old technology engine too, align with motorcycle engine technology development trends led by major OEMs. Instant engine protection from heat-activated anti-wear molecule™ can make engine protected from the start of the engine to the high temperature conditions caused by long, continuous driving.

### Features and Benefits

- Mobil Super Moto 20W-40 is made of highly refined, quality mineral oils and an advanced additive system.
- Balanced quality oil and additives enables keep engine clean without corrosion, protecting engine and gearbox in one circulation system.
- Hi traction of Mobil Super Moto 20W-40 prevents clutch slippage.
- Instant engine protection from heat-activated anti-wear molecule™.
- 57% more wear protection against industry standard based on Industry standard engine test Sequence IVA in API SL

### Applications

- Best for the modern four-stroke motorcycle engines JASO MA or JASO MA2 recommended by OEMs.
- Good protection to motorcycle engines before introduction of JASO MA or JASO MA2.

### Specifications and Approvals

This product meets or exceeds the requirements of the following industry specification:
JASO MA
JASO MA2
JASO MA
JASO MA2
API SL

### Properties and Specifications

Property	
Grade	SAE 20W-40
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	15
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	122

Property	
Density @ 15.6 C, g/ml, ASTM D4052	0.88
Pour Point, °C, ASTM D97	-30
Flash Point, °C, ASTM D92	230
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	5.9
Mini-Rotary Viscometer, Apparent Viscosity, -20 C, mPa.s, ASTM D4684	12500
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	4.1

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved