



MOBIL 1™ C40 GT 0W-40

Mobil Passenger Vehicle Lube , Sri Lanka

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1™ C40 GT 0W-40 is an advanced full synthetic engine oil specifically engineered for high performing Porsche GT Engines. Mobil 1™ C40 GT 0W-40 has been designed to protect the engine from wear in extreme conditions and prevent sludge formation. It is the technology developed within the framework of the collaboration established with Porsche AG for over the last 25 years.

Features and Benefits

Mobil 1™ C40 GT 0W-40 is made with a proprietary blend of leading edge components formulated to be fully compatible with Porsche GT engines. Mobil 1™ C40 GT 0W-40 has been designed to help deliver outstanding performance and protection in extreme conditions. It is distinguishable by its unique green colour. Key features and potential benefits¹ include:

Features	Advantages and Potential Benefits
Outstanding high-temperature thermal and oxidation stability	Helps to reduce oil aging for protection throughout your oil drain interval
High temperature oil film resistance	Contributes to outstanding wear protection
Enhanced frictional properties	Helps improve fuel economy ²
Active cleaning agents	Contributes to deliver outstanding engine cleanliness and sludge control

Applications

Mobil 1 C40 GT 0W-40 is specifically designed for Porsche GT engines requiring C40 GT specification³. Mobil 1 C40 GT 0W-40 is required by Porsche for the following models:

- 911 GT3 (991 and newer)
- 911 GT3 Cup (991/992)
- 911 GT3 R (991/992)
- 911 GT3 RS (991 and newer)
- 911 RSR (991)
- 911 R (991)
- 911 Speedster (991)
- 911 S/T (992)

- 718 Cayman GT4 RS (982)
- 718 Cayman GT4 RS Clubsport (982)
- 718 Spyder RS (982)

Mobil 1 C40 GT 0W-40 is not suitable for Porsche vehicles requiring an A40, C20, C30 or C40 approved Mobil 1 engine oils.

Notes

1: Based on industry and OEM standard engine tests.

2: Actual savings are dependent upon vehicle and engine type, outside temperature and barometric pressure, driving conditions and your current engine oil viscosity.

3: Always consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and specifications.

Specifications and Approvals

This product has the following approvals:
Porsche C40 GT

Properties and Specifications


Property	
Grade	SAE 0W-40
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	20700
Viscosity Index, ASTM D2270	199
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	72
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.8
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁽⁶⁾ sec ⁽⁻¹⁾ , mPa.s, ASTM D4683	3.8
Density @ 15 C, g/ml, ASTM D1298	0.846
Flash Point, Cleveland Open Cup, °C, DIN EN ISO 2592	230
Total Base Number, mgKOH/g, ASTM D2896	8.3
Pour Point, °C, ASTM D97	-48

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

The ExxonMobil logo is displayed in white on a dark background. It consists of the word "Exxon" in a bold, sans-serif font, followed by "Mobil" in a similar font, with a stylized "X" connecting the two words.A row of four logos is shown in white on a dark background. From left to right: the "Exxon" logo, the "Mobil" logo, the "Esso" logo (a circle with the word "Esso" inside), and the "XTO ENERGY" logo (the letters "XTO" in a large, bold font with "ENERGY" in a smaller font below it).

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved