



Mobil 1™ 10W-60

Mobil Passenger Vehicle Lube , Lithuania
Advanced Full Synthetic Motor Oil

Product Description

Mobil 1 is the world's leading synthetic motor oil brand delivering our ultimate performance and protection.

Mobil 1 10W-60 Advanced Full Synthetic Motor Oil is formulated for the specific demands of older vehicles even above 150,000 km. Mobil 1 10W-60 is also suitable for high performance and motorsport applications requiring high viscosity motor oils.

Features and Benefits

Mobil 1 10W-60 Advanced Full Synthetic Motor Oil is made with a proprietary blend of ultra high performance synthetic basestocks fortified with a precisely balanced component system. Mobil 1 10W-60 is engineered to help provide long lasting protection in higher mileage engines for long life out of your vehicle.

- Extra seal conditioners to help prevent oil leaks
- Provides exceptional cleanliness and removes existing sludge
- Outstanding/Excellent oil film thickness for extra protection in older engines
- High viscosity to help reduce oil burn off in older engines
- More anti-wear additives to help protect worn engines
- High performance basestocks for excellent all-round wear protection

Applications

Mobil 1 10W-60 has been designed to help provide the extra protection that older engines can demand. It is suitable for most older vehicles including gasoline and (without Diesel Particulate Filter) engines.

- Older vehicles
- Nearly all operating conditions, from mild to extreme
- An ideal product for racing applications

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
VW 501 01
VW 505 00
This product is recommended for use in applications requiring:
API CF
MB 229.1

This product meets or exceeds the requirements of:
API SN
API SM
API SL
API SJ
ACEA A3/B3
ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 10W-60
Density @ 15 C, g/cm3, ASTM D4052	0.855
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	22.7
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	156
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTON

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved