



Mobil Super™ 3000 Formula LD 0W-30

Mobil Passenger Vehicle Lube , Lithuania

Fully synthetic motor oil

Product Description

Mobil Super™ 3000 Formula LD 0W-30 is a fully synthetic motor oil for gasoline and light duty diesel engines. It is designed to meet the demanding requirements for extended service life and to make a significant contribution to fuel economy and engine cleanliness.

Features and Benefits

Mobil Super 3000 Formula LD 0W-30 provides the following features and benefits:

- Fully synthetic formulation provides extended oil drain capability in VW-Audi cars using the long service schedule (EDI) associated with VW 506 01 specifications
- Excellent low temperature fluidity provides rapid circulation and wear protection at start-up particularly when cold
- Excellent oxidation and thermal stability provide protection when exposed to high temperature and demanding service

Applications

Mobil Super 3000 Formula LD 0W-30 should be used in VW and Audi vehicles operating under the specific service oil drain recommendations associated with VW 506 01 specifications. These vehicles will already have been filled with an oil of this quality at the factory.

Specifications and Approvals

Mobil Super 3000 Formula LD 0W-30 has the following builder approvals:	
Volkswagen	VW 506 01

Typical Properties

Mobil Super 3000 Formula LD 0W-30	
Viscosity, ASTM D 445	
cSt @ 40° C	53
cSt @ 100° C	9.6
Sulphated Ash, wt%, ASTM D 874	-
Phosphorous	-
Flash Point, °C, ASTM D 92	223
Density @15° C kg/l, ASTM D 4052	0.86
Pour Point, °C, ASTM D 97	-39

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Super are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

05-2023

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect

product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved