



MOBIL SUPER 3000 FORMULA M 5W40

Mobil Passenger Vehicle Lube , Latvia

Advanced Synthetic Technology Engine Oil

Product Description

Mobil Super 3000 Formula M 5W-40 is an advanced synthetic technology engine oil primarily intended for use in Mercedes Benz vehicles where a long-life product for extended service intervals is required.

Features and Benefits

Mobil Super 3000 Formula M 5W-40 provides the following features and benefits:

- Permits extended operation at elevated temperatures without significant oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in gasoline and diesel engine passenger cars and light commercial vehicles without particulate filters.

Applications

Mobil Super 3000 Formula M 5W-40 has been developed to meet the highest specifications for engine oils required by Mercedes Benz. It offers excellent performance at both very low and very high operating temperatures and long term engine protection from wear and sludge.

Always consult your owner's manual to check the recommended oil drain interval, viscosity grade and specifications for your vehicle.

Specifications and Approvals

| This product has the following approvals: |
|---|
| MB-Approval 229.3 |
| MB-Approval 229.5 |

| This product meets or exceeds the requirements of: |
|--|
| API SL |
| API SM |
| API SN |
| API SN PLUS |
| API SP |

This product meets or exceeds the requirements of:

ACEA A3/B4

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-40 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 13.1 |
| Pour Point, °C, ASTM D97 | -36 |
| Viscosity Index, ASTM D2270 | 169 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.846 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 78 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 236 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>


All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved