



Mobil Super 15W-50

Mobil Passenger Vehicle Lube , Morocco

Premium Multigrade Passenger Vehicle Engine Oil

Product Description

An extra high performance motor oil for all types of vehicles, providing ultimate engine protection up to 5000 KM. The heat activated anti-wear molecule protect engine against wear and corrosion, ensuring long engine life.

Features and Benefits

Mobil Super 15W-50 provides engine protection and helps promote long engine life:

- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super 15W-50 has been formulated to be suitable for use in vehicles requiring an API SL, API SN, API SM and API SJ claims . ExxonMobil particularly recom Mobil Super 15W-50 for daily driving:

- Under normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

| |
|--|
| According to ExxonMobil, this product is of the following quality level: |
| API CF |

| |
|--|
| MOBIL SUPER 15W-50 meets or exceeds the requirements of: |
| API SJ |
| API SL |
| API SM |
| API SN |

Properties and Specifications

| Property | |
|---|------------|
| Grade | SAE 15W-50 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 17.95 |

| Property | |
|---|--------|
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 139.5 |
| Viscosity Index, ASTM D2270 | 144 |
| Ash, Sulfated, mass%, ASTM D874 | 0.91 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 4.68 |
| Pour Point, °C, ASTM D97 | -30 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 226 |
| Density @ 15 C, g/ml, ASTM D4052 | 0.8768 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved