



Mobil™ Coolant Extra Ready Mixed 33%

Mobil Ancillary , Republic of Madagascar

High Performance Coolant

Product Description

Mobil™ Coolant Extra Ready Mixed 33% is a high-performance coolant designed to provide efficient protection in all seasons. It is a ready to use product that has been premixed with antifreeze and water.

Mobil™ Coolant Extra Ready Mixed 33% contains Glyscantin® G48® engine coolant concentrate based on ethylene glycol fluid that contains a mixture of inorganic (silicate) and organic corrosion inhibitors, free of nitrites, amines, and phosphates.

Mobil™ Coolant Extra Ready Mixed 33% acts as both antifreeze and coolant and imparts very good anticorrosion protection to all metal parts found in the cooling systems of internal combustion engines.

Features and Benefits

Mobil™ Coolant Extra Ready Mixed 33% provides following benefits:

- Colored blue green for easy recognition helping avoid usage errors.
- Outstanding protection against frost and overheating in all modern engines, but especially highly loaded aluminum engines.
- Effective protection against corrosion and deposits in the cooling system vital parts.
- Easy circulation through the engine block and cylinder head channels, the radiator, and the heater enabling cooler operation and protection of the engine.

Applications

Brand	Specification
VW/Audi/Seat/Skoda	TL 774-C
BMW/Mini/Rolls Royce	BMW LC-87
MB/Smart	MB-325.0
Opel	B 40 240
Volvo Trucks	TR 1286083
MAN Truck & Bus	MAN 324 Typ NF
Daimler Truck & Buses	MB-325.0

*: Refer to BASF Glyscantin® G48® webpage for latest and additional usage recommendations in other passenger and commercial vehicles.

Always consult your owner's manual to check recommended product and specifications for your particular vehicle.

Properties and Specifications

Property	
Grade	N/A
Density @ 15.6 C, g/cm ³ , ASTM D4052	1.052
Color, Visual	Greenish Blue

Property	
pH, ASTM D1287	8
Appearance, Visual	Clear

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2024

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved