



Mobil Super™ 1000 20W-50

Mobil Passenger Vehicle Lube , Republic of Madagascar

Premium Multigrade Passenger Vehicle Engine Oils

Product Description

Mobil Super 1000 20W-50 is a premium quality mineral motor oils. The product is designed to provide protection for your engine under most operating conditions

Features and Benefits

Mobil Super 1000 provides engine protection and helps promote long engine life.

- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super 1000 20W-50 has been formulated to be suitable for use in vehicles requiring an API SL claim . ExxonMobil particularly recommend Mobil Super 1C daily driving under normal conditions:

- Passenger cars, SUV's, light trucks and vans (Gasoline engines) requiring an API SL
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:	
API SL	

Properties and Specifications

Property	
Grade	SAE 20W-50
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	19
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	174
Pour Point, °C, ASTM D97	-27
Viscosity Index, ASTM D2270	124
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.7
Flash Point, Cleveland Open Cup, °C, ASTM D92	240

Property	
Density @ 15 C, g/ml, ASTM D4052	0.8928

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2023

ExxonMobil

Exxon

Mobil

Esso

ATOMOBIL

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved