



## MOBIL 1 FS 5W40

Mobil Passenger Vehicle Lube , Myanmar

Advanced Full Synthetic Engine Oil

### Product Description

Mobil 1™ Triple Action Power advanced full synthetic engine oil delivers outstanding engine Performance, Protection, and Cleanliness.

### Features and Benefits

Why these matter for your engine:

- PERFORMANCE: Reduces the stress of daily wear and harsh conditions for longer engine life.
- PROTECTION: Guards against extreme temperatures to prevent breakdowns.
- CLEANLINESS: Prevents buildup of contaminants and sludge for a cleaner engine.

Mobil 1™ Triple Action Power is feature packed to:

- PERFORM: Keeps your engine running like new.
- PROTECT: 10X\* better protection for high temperatures.
- CLEAN: Fights sludge with active cleaning agents.

\*Based on Sequence IIIH, against API SP specification.

### Applications

Mobil 1™ Triple Action Power is suitable for use in petrol, diesel, and hybrid vehicles.

Always check your owner's manual for the recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product has the following approvals:
MB-Approval 229.3
MB-Approval 229.5
VW 502 00
VW 505 00
BMW Longlife 01
RENAULT RN0700
RENAULT RN0710
Porsche A40

**This product is recommended for use in applications requiring:**

API CF

**This product meets or exceeds the requirements of:**

Fiat 9.55535-M2

API SP

API SN PLUS

API SN

API SM

ACEA A3/B4

### Properties and Specifications

Property	
Grade	SAE 5W-40
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	22000
Pour Point, °C, ASTM D97	-40
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.7
Total Base Number, mgKOH/g, ASTM D2896	12.5
Ash, Sulfated, mass%, ASTM D874	1.1
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	81
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.2
Viscosity Index, ASTM D2270	170
Density @ 15.6 C, g/ml, ASTM D4052	0.841
Flash Point, Cleveland Open Cup, °C, ASTM D92	241

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved