



Mobil Super™ 1000 10W-40

Mobil Passenger Vehicle Lube , Mongolia

Synthetic Technology Engine Oil

Product Description

Mobil Super™ 1000 10W-40 is premium synthetic technology motor oil designed to provide everyday protection for cars under most operating conditions.

Features and Benefits

Mobil Super 1000 10W-40 is meticulously engineered for today's tougher engine specifications. It provides reliable engine protection in everyday driving and helps to extend engine life.

- Designed to provide reliable anti-wear protection
- Proven Protection against LSPI (low speed pre-ignition) events in TGDI engines to help prolong engine life
- Helps to maintain engine cleanliness

Applications

Mobil Super 1000 10W-40 is suitable for use in both gasoline and diesel powered vehicles, ideally suited for less stressful driving conditions such as highway driving and lower consistent speed conditions in everyday driving.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

| This product meets or exceeds the requirements of: |
|--|
| API SL |
| API SM |
| API SN |
| API SN PLUS |
| API SP |

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 10W-40 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 13 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 91 |

| Property | |
|---|-------|
| Viscosity Index, ASTM D2270 | 142 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.868 |
| Pour Point, °C, ASTM D97 | -33 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 221 |
| Ash, Sulfated, mass%, ASTM D874 | 0.8 |
| Total Base Number, mgKOH/g, ASTM D2896 | 7.5 |
| Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684 | 20600 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 3.6 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved