



Mobil Delvac Modern™ 10W-30 Fuel Efficient

Mobil Commercial Vehicle Lube , Mexico

Synthetic Diesel Engine Oil

Product Description

Mobil Delvac Modern™ 10W-30 Fuel Efficient is a synthetic diesel engine oil that helps extend engine life, allowing you to run your business with confidence. It meets or exceeds the new API FA-4 specification for fuel efficient engine oils as well as key original equipment manufacturer (OEM) requirements.

Mobil Delvac Modern 10W-30 Fuel Efficient is engineered to deliver potential fuel economy benefits¹ beyond those typically provided by SAE 10W-30 engine oils. This product is a tailored formulation that delivers excellent wear and engine protection, extended drain capability, outstanding high temperature performance and engine cleanliness. Developed in close collaboration with major OEMs, Mobil Delvac Modern 10W-30 Fuel Efficient is recommended for use in heavy duty applications and operating environments found in the on-road trucking industry.

Mobil Delvac Modern 10W-30 Fuel Efficient should only be used where an API FA-4 oil is recommended by the OEM. Before using this product in an engine, users should consult recommendations as shown in an owner's manual or other service bulletins.

Features and Benefits

Mobil Delvac Modern 10W-30 Fuel Efficient is formulated with synthetic oil, containing hydro-processed base stocks and a tailored additive system to deliver extended performance for up to 50% beyond OEM-recommended oil drain intervals¹. The proprietary formulation delivers excellent wear protection, superior oxidation stability, and outstanding TBN retention. Mobil Delvac Modern 10W-30 Fuel Efficient also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

Mobil Delvac Modern 10W-30 Fuel Efficient is engineered to provide greater potential fuel economy benefits than typical SAE 10W-30 oils².

Features	Advantages and Potential Benefits
Potential to improve fuel economy ²	Engineered to provide greater potential fuel economy benefits than typical SAE 10W-30 oils
Superior oxidation stability	Extended ODI capability ¹ . Reduced low temperature sludge build-up and high temperature deposits
Excellent soot and viscosity control	Greater engine efficiency, long engine life and long oil life
Excellent oil consumption control	Lower oil costs due to less make-up oil during operation
Outstanding TBN reserves	Corrosion protection and extended drain intervals for both new and old engines using up to 500 ppm sulfur diesel fuel
Low temperature fluidity and pumpability	Formulated for smooth starting in cold weather
Resistance to corrosive and abrasive wear	Long life of critical wear surfaces
Component compatibility	Long gasket and seal life
Low ash formulation meeting API FA-4 requirements	Long emissions aftertreatment life (DPF, DOC and SCR)
Meets API SN	Suitable for use in gasoline engines requiring an oil meeting the API SN specification

¹ Based on US engine manufacturers' (OEM) average oil drain intervals (ODI) API CK-4 / API FA-4 recommendation. Results may vary based on vehicle/engine condition, driving and environmental conditions Consult OEM or ExxonMobil before implementing extended ODI.

² Compared to CK4 specification. Results vary based on vehicle/engine condition, driving and environmental conditions.

Applications

- Formulated for use in the latest heavy duty diesel engines, where API FA-4 is recommended by the OEM.
- Engines equipped with emission control systems including exhaust aftertreatment systems.
- On-highway applications operating in both high speed/high load and short haul pick-up/delivery service.

Specifications and Approvals

This product has the following approvals:

Detroit Detroit Fluids Specification 93K223

This product meets or exceeds the requirements of:

API FA-4

API SN

JASO DH-2

Properties and Specifications

Property	
Grade	SAE 10W-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	218
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	64.1
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.8
Viscosity Index, ASTM D2270	137
Density @ 15 C, g/ml, ASTM D1298	0.87
Pour Point, °C, ASTM D97	-33

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved