



## Mobil Delvac Legend™ 20W-50 High Mileage

Mobil Commercial Vehicle Lube , Mexico

High Performance Diesel Engine Oil

### Product Description

The technology behind Mobil Delvac Legend™ 20W-50 High Mileage provides excellent performance in both modern and older diesel engines.

Mobil Delvac Legend™ 20W-50 High Mileage is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying and agricultural industries.

### Features and Benefits

More than 90 years of experience and innovation supports the technology in Mobil Delvac Legend™ 20W-50 High Mileage. Delivers excellent performance in both naturally aspirated as well as turbo-charged diesel-powered equipment. The key benefits include:

| Features   | Advantages and Potential Benefits  |
|--|--|
| Thermal and oxidation stability                  | Controls sludge build-up and deposits  |
| TBN reserve                                      | Deposit control and acid neutralization  |
| High Viscosity and Stay-in-grade shear stability | Reduced oil consumption, increased wear protection and high oil pressure across a wide operating temperature range |
| Excellent detergency/dispersancy                 | Cleaner engines and prolonged engine life  |
| Component compatibility                          | Long gasket and seal life  |

### Applications

- Naturally aspirated and turbo-charged diesel-powered equipment European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including construction, mining, quarrying, and agriculture

### Specifications and Approvals

|   |
|---|
| <b>This product meets or exceeds the requirements of:</b> |
| API CH-4  |

### Properties and Specifications

|                 |  |
|-----------------|--|
| <b>Property</b> |  |
|-----------------|--|

| Property   |            |
|--|------------|
| Grade  | SAE 20W-50 |
| Pour Point, °C, ASTM D97                                   | -36        |
| Density @ 15.6 C, g/ml, ASTM D4052                         | 0.889      |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 18.7       |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved