



Mobil Super™ FE Ahorra Combustible
Mobil Passenger Vehicle Lube , Mexico
Premium Automotive Engine Oil

Product Description

Mobil Super™ FE Ahorra Combustible Oils are formulated from high quality base stocks combined with modern performance additives to give your engine the proven protection and performance you expect under a wide variety of operating conditions for long engine life. . This advanced technology lubricant contains performance additives to help protect engines for 7,500 kilometers between oil changes or 6 months, whichever comes first. These motor oils also deliver greater fuel efficiency since they are classified by the API as “Resource Conserving” engine lubricants, and meet or exceed the latest industry specification ILSAC GF-5 / API SN. Those claims are backward compatible with earlier performance levels such as API SM, SL, and SJ and previous ILSAC categories.

Mobil Super FE Ahorra Combustible Oils are available in two multi-viscosity grades: SAE 5W-20 and 5W-30.

Features and Benefits

- Helps extend engine life
 - Improved fuel economy of up to 3%*
 - Proven protection of critical engine parts for 7,500 kilometers or 6 months, whichever comes first**
 - Excellent engine cleanliness
 - Engine protection under a wide variety of operating conditions
 - API SN / Resource Conserving
 - Helps reduce engine wear and deposits
 - Meets or exceeds the latest industry specification (ILSAC GF-5 / API SN)
 - Easy cold starting
- * The estimate Fuel Economy is based on a comparison with those viscosity grades most commonly used. The actual savings will depend on the type of vehicle and engine, outside temperature, driving conditions and the currently used viscosity.
- **The possibility of extending the times between oil changes does not apply under the following conditions: automobile races and commercial use, frequent haulage or cargo transport, excessive dirt or frequent operation in lowest gear. If your vehicle is covered by a warranty, follow the recommended oil change interval

Applications

Mobil Super FE Ahorra Combustible Oils are recommended for gasoline fueled automobiles and light duty trucks requiring an API SN, SM, SL or SJ. They also meet ILSAC GF-5 (Starburst Certification Symbol).

Before using a Mobil Super FE Ahorra Combustible motor oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

Mobil Super FE Ahorra Combustible meets or exceeds the requirements of :	5W-20	5W-30
API SN	X	X
API SM	X	X
API SL	X	X
API SJ	X	X
ILSAC GF-5	X	X

Mobil Super FE Ahorra Combustible meets or exceeds the requirements of :	5W-20	5W-30
Ford WSS-M2C945-A	X	
Ford WSS-M2C946-A		X

Mobil Super FE Ahorra Combustible is recommended by ExxonMobil for use in applications requiring:	5W-20	5W-30
Ford WSS-M2C930-A	X	
Ford WSS-M2C929-A		X

Typical Properties

Mobil Super FE Ahorra Combustible	5W-20	5W-30
API Service Classification	SN	SN
Gravity, API	33.1	33
Specific Gravity	0.8596	0.86
Pour Point, °C (°F)	-36(-33)	-36(-33)
Flash Point, °C (°F), ASTM D 92	224(435)	220(428)
Viscosity		
cSt at 40°C	49.2	60.42
cSt at 100°C	8.6	10.2
CCS, cP	5800@-30 °C	6100@-30 °C
MRV, cP	26,400@-35 °C	29,330@-35 °C
Viscosity Index	153	157
Resource Conserving	YES	YES

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment

Mobil, the Mobil logotype and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved