



Mobil Super™ Moto 4T 20W-50

Mobil Passenger Vehicle Lube , Mexico

High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super Moto 4T™ 20W-50 is a high performance conventional four-stroke motorcycle engine oil primarily intended for general use in many types of four-motorcycles and engines.

Features and Benefits

Mobil Super Moto™ 4T 20W-50 combines highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear prot and corrosion protection. Key features and benefits include:

Features	Advantages and Potential Benefits
Good wear protection	Helps extend engine life
Thermal and oxidation stability	Helps keep engines clean for smoother operation
Good corrosion protection	Protects critical engine components

Applications

Mobil Super Moto™ 4T 20W-50 is recommended for use in the modern four-stroke motorcycle engines requiring JASO MA or JASO MA2 with API SL recommen OEMs.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
JASO MA
JASO MA2

Properties and Specifications

Property	
Grade	SAE 20W-50
Flash Point, °C, ASTM D92	246
Viscosity Index, ASTM D2270	130
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	146.7
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	17.4

Property	
Density @ 15 C, g/ml, ASTM D1298	0.88
Pour Point, °C, ASTM D97	-30
Phosphorus, mass%, ASTM D4951	0.089
Ash, Sulfated, mass%, ASTM D874	0.75

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023
ExxonMobil Mexico, S.A. de C.V.
Poniente 146 No. 760 Col. Industrial Vallejo
C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

Xtreme

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved