



Mobil Super™ TRC - PRO

Mobil Passenger Vehicle Lube , Mexico

Conventional Engine Oil

Product Description

Mobil Super™ TRC - PRO Oils are conventional high-viscosity multigrade engine oils that provide extra protection to your engine, delivering 35% better wear protection than industry standards* giving your engine the proven protection and performance you expect under a wide variety of operating conditions for long engine life.

Mobil Super TRC - PRO oils contain TRC that is heat activated and help maintain the optimal viscosity, surpassing the protection expectations for high viscosity quality SN category approved gasoline engine oils.

Mobil Super TRC - PRO Oils are available in four multi-viscosity grades: SAE 15W-40 (API SN), 20W-50 (API SN), 5W-30 (API SN) and 10W-30 (API SN). Those are backward compatible with earlier performance levels such as API SM, SL, and SJ and previous ILSAC categories.

Features and Benefits

- 35% better wear protection against industry standards*
- Helps extend engine life
- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Helps reduce engine wear and deposits
- Meets or exceeds the latest industry specification API SN

*Better wear protection compared to API SN engine test requirement in ASTM D6891 Seq. IVA test

Applications

Mobil Super TRC - PRO Oils are recommended for current and earlier gasoline fueled passenger cars, sport utility vehicles, vans and light duty trucks where a viscosity API SN, SM, SL or SJ oil is preferred or recommended.

Mobil Super TRC - PRO 20W-50 has a higher viscosity which provides engines with full protection under higher operating speeds, higher ambient temperature and other adverse conditions.

Before using a Mobil Super TRC - PRO motor oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

This product is recommended for use in applications requiring:	MOBIL SUPER TRC - PRO 5W-30	MOBIL SUPER TRC - PRO 10W-30	MOBIL SUPER TRC - PRO 15W-40
Ford WSS-M2C929-A	X		

This product meets or exceeds the requirements of:	MOBIL SUPER TRC - PRO 5W-30	MOBIL SUPER TRC - PRO 10W-30	MOBIL SUPER TRC - PRO 15W-40
API SJ	X	X	

This product meets or exceeds the requirements of:	MOBIL SUPER TRC - PRO 5W-30	MOBIL SUPER TRC - PRO 10W-30	MOBIL SUPER TRC - PRO 15W-40
API SL	X	X	X
API SM	X	X	X
API SN	X	X	X
Ford WSS-M2C946-A	X		
Ford WSS-M2C946-B1	X		

Properties and Specifications

Property	MOBIL SUPER TRC - PRO 5W-30	MOBIL SUPER TRC - PRO 10W-30	MOBIL SUPER TRC - PRO 15W-40
Grade	SAE 5W-30	SAE 10W-30	SAE 15W-40
Density @ 15.6 C, g/ml, ASTM D4052	0.858	0.867	
Flash Point, Cleveland Open Cup, °C, ASTM D92	225	228	237
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.5	10.7	14.9
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	64	73	108
Pour Point, °C, ASTM D97	-42	-39	-30

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021
ExxonMobil Mexico, S.A. de C.V.
Poniente 146 No. 760 Col. Industrial Vallejo
C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved