



Mobil Monogrado Series

Mobil Passenger Vehicle Lube , Mexico

Conventional Monograde Engine Oil

Product Description

Mobil™ Monogrado 40 is a heavy duty engine oil primarily intended for use in gasoline automotive engines of passenger cars. It's formulated from high quality mineral base oils and an advanced additive system required for combustion engines where an API SL engine oil is recommended. It contains an effective balance of detergents and dispersants to minimize the formation of sludge and deposits, retain alkalinity (TBN) and reduce wear.

Features and Benefits

- Help promote engine cleanliness.
- Good protection against wear and corrosion.
- Extended intervals between oil drain.
- Low oil consumption."

Applications

Mobil Monogrado 40 is recommended for the lubrication of gasoline engines for passenger cars. It can also be used in gear and hydraulic applications if the builder approves the use of monogrades engine oils for these applications.

Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:	MOBIL MONOGRADO 40	MOBIL MONOGRADO 50
API SG		X
API SH		X

This product is recommended for use in applications requiring:	MOBIL MONOGRADO 40	MOBIL MONOGRADO 50
API SG	X	
API SH	X	

This product meets or exceeds the requirements of:	MOBIL MONOGRADO 40	MOBIL MONOGRADO 50
API SJ	X	X
API SL	X	X

Properties and Specifications

Property	MOBIL MONOGRADO 40	MOBIL MONOGRADO 50
Grade	SAE 40	SAE 50

Property	MOBIL MONOGRADO 40	MOBIL MONOGRADO 50
Density @ 15 C, g/ml, ASTM D1298	0.892	
Density @ 15 C, g/ml, ASTM D4052	0.896	0.901
Flash Point, Cleveland Open Cup, °C, ASTM D92	270	277
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	218	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.8	19.6
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	150.7	214
Pour Point, °C, ASTM D97	-17	-27

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved