



## Mobil Special 40 50

Mobil Passenger Vehicle Lube , Mexico

Added Performance Engine Oil

### Product Description

Mobil Special 40, 50 Series are heavy duty engine oils primarily intended for use in gasoline automotive engines of passenger cars. They are formulated from high quality mineral base oils and an advanced additive system required for combustion engines where an API SL engine oil is recommended. . They contain an effective balance of detergents and dispersants to minimize the formation of sludge and deposits, retain alkalinity (TBN) and reduce wear.

### Features and Benefits

- Help promote engine cleanliness.
- Good protection against wear and corrosion.
- Extended intervals between oil drain.
- Low oil consumption.

### Applications

Mobil Special 40, 50 Series are recommended for the lubrication of gasoline engines for passenger cars. They can also be used in gear and hydraulic applications if the builder approves the use of monogrades engine oils for these applications.

### Specifications and Approvals

This product meets or exceeds the requirements of:	MOBIL SPECIAL 40	MOBIL SPECIAL 50
API SL	X	X

### Properties and Specifications

Property	MOBIL SPECIAL 40	MOBIL SPECIAL 50
Grade	SAE 40	SAE 50
Ash, Sulfated, mass%, ASTM D874	0.79	0.79
Flash Point, Cleveland Open Cup, °C, ASTM D92	256	262
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.7	19.5
Pour Point, °C, ASTM D97	-27	-27
Total Base Number, mgKOH/g, ASTM D2896	7.2	

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico


(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved