



Mobil Super Moto™ Scooter MX 10W-40

Mobil Passenger Vehicle Lube , Mexico

Synthetic Technology Four-Stroke Scooter Engine Oil

Product Description

Mobil Super Moto™ Scooter MX 10W-40 is a high performance, semi-synthetic four-stroke scooter engine oil developed for modern scooters.

Features and Benefits

Mobil Super Moto™ Scooter MX 10W-40 is specially designed to smooth acceleration required in city traffic conditions with minimal vibrations.

Additionally, Mobil Super™ Moto Scooter MX 10W-40 provides superior protection even to high capacity engines when compared to API SL requirements.

Features	Advantages and Potential Benefits
Synthetic technology	Advanced formulation for performance in extreme conditions
Excellent wear protection	Longer engine component and overall engine life
Good thermal, oxidation stability and deposit control	Cleaner running engines resulting in smooth flawless operation
Excellent corrosion protection properties	Longer life of valve train and bearing components
Enhanced low temperature properties	Easier cold weather starting, longer electrical system life
Low friction in engine moving parts	Smooth accelerations and low vibrations

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
JASO MB

Properties and Specifications

Property	
Grade	SAE 10W-40
Flash Point, Cleveland Open Cup, °C, ASTM D92	229
Viscosity Index, ASTM D2270	147
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	93.8

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.6
Density @ 15 C, g/ml, ASTM D1298	0.86
Pour Point, °C, ASTM D97	-42
Phosphorus, mass%, ASTM D4951	0.085
Ash, Sulfated, mass%, ASTM D874	0.79

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved