



## Mobilube™ HD 80W-90

Mobil Commercial Vehicle Lube , Malaysia

Heavy Duty Automotive Gear Lubricants

### Product Description

Mobilube HD 80W-90 is high performance, heavy duty gear lubricant formulated from high performance base oils and an advanced additive system. The lubricant is engineered for automotive applications including heavy duty axles and final drives where extreme pressures and shock loading are expected. It is recommended by ExxonMobil for applications where API GL-5 service is required.

### Features and Benefits

Today's heavy equipment applications place higher performance demands on drive train lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and optimise operating costs. Longer service intervals place additional demands on the gear lubricant requiring effective basestock and additive systems. Mobilube HD 80W-90 is engineered to meet these challenges. The key benefits include:

Features	Advantages and Potential Benefits
Exceptional thermal stability and resistance to high temperature oxidation	Extended gear and bearing life due to minimal deposits Longer seal life
Outstanding protection against low speed/high torque wear and against high speed scoring	Increased load carrying capability Reduced maintenance costs and longer equipment life
Excellent rust and corrosion protection	Reduced wear and longer component life
Effective low temperature lubrication	Improved startability
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination

### Applications

Recommended by ExxonMobil for use in:

- Heavy duty axles and final drives requiring API GL-5 level performance.
- Passenger cars, on highway light and heavy duty trucks and commercial vehicles.
- Off highway industries including: construction, mining, quarrying, and agriculture.
- Other heavy duty industrial and automotive applications involving hypoid gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque prevail.

### Specifications and Approvals

<b>This product meets or exceeds the requirements of:</b>
API GL-5

### Properties and Specifications

Property	
Grade	SAE 80W-90
Brookfield Viscosity @ -26 C, mPa.s, ASTM D2983	120000
Density @ 15 C, g/ml, ASTM D4052	0.87
Flash Point, °C, ASTM D92	220
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.5
Pour Point, °C, ASTM D97	-30
Viscosity Index, ASTM D2270	97
Shear Stability (KRL 20h), mm <sup>2</sup> /s, CEC L-45-A-99	14

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

1-800-81-6233

SEALubeline@exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved