



## Mobil HD

Mobil Passenger Vehicle Lube , Malaysia

Added Performance Engine Oil

### Product Description

Mobil HD Series are high performance heavy duty engine oils primarily intended for use in gasoline automotive engines of passenger cars, commercial vehicles and farm equipment. They may also be used in diesel engines of commercial vehicles and contractor equipment. They are formulated from high quality mineral base oils and an advanced additive system to provide the excellent performance required for modern combustion engines. They contain an effective balance of detergents and dispersants to minimize the formation of sludge and deposits, retain alkalinity (TBN) and reduce wear.

### Features and Benefits

- Improved engine cleanliness.
- Good protection against wear and corrosion.
- Extended intervals between oil drain.
- Low oil consumption.
- Reduced inventory costs for mixed fleet operations.

### Applications

Mobil HD Series are recommended for the lubrication of gasoline engines for passenger cars, commercial vehicles and farm equipment as well as diesel engines for commercial vehicles and contractor equipment. They can also be used in gear and hydraulic applications if the builder approves the use of engine oils.

### Specifications and Approvals

This product is recommended for use in applications requiring:	40
API CC	X
API SF	X

### Properties and Specifications

Property	40
Grade	SAE 40
Ash, Sulfated, mass%, ASTM D874	0.82
Flash Point, °C, ASTM D92	247
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	15.5
Pour Point, °C, ASTM D97	-21
Total Base Number, mgKOH/g, ASTM D2896	7.1

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2021

1-800-81-6233

SEALubeline@exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved