

Mobil Super 3000 Formula 5W30

Mobil Passenger Vehicle Lube, New Caledonia

High performance motor oil

Product Description

Mobil Super™ 3000 Formula 5W-30 is an ACEA C1 low ash high performance motor oil designed to help prolong the life and maintain the efficiency of the Exhaust Car Emission Reduction Systems in both diesel and gasoline powered automobiles

Features and Benefits

Mobil Super 3000 Formula 5W-30 offers excellent performances at both low and high operating temperatures and long term engine protection. Key features and benefits include:

- •Helps maintain efficiency of Diesel particulate filters and gasoline catalytic convertors
- •Protects engines from wear and deposit build-up
- •Helps fuel economy through reduced friction
- •Suitable for use in both gasoline and diesel passenger cars and light commercial vehicles

Applications

Mobil Super 3000 Formula 5W-30 is recommended by ExxonMobil for applications requiring Ford WSS-M2C934-B and Jaguar Land Rover STJLR.03.5005 which includes Jaguar and Land Rover vehicles from January 2009 fitted with the 3.0 Litre V6 Diesel engine, and Mazda Diesel engines fitted with Diesel Particulate Filter (DPF) from 2005

Specifications and Approvals

This product has the following approvals:	
STJLR.03.5005	

This product meets or exceeds the requirements of:

ACEA C1

Ford WSS-M2C934-B

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	9.4
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	50
Density @ 15 C, g/ml, ASTM D4052	0.848

Property	
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Ash, Sulfated, mass%, ASTM D874	0.4
Phosphorus, mass%, ASTM D4951	0.045

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise. 05-2020

