



Mobil Super™ Moto 4T 20W-50

Mobil Passenger Vehicle Lube , Nigeria

High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super Moto 4T 20W-50 is a high performance conventional four-stroke motorcycle engine oil primarily intended for general use in many types of four-stroke motorcycles and engines.

Features and Benefits

Mobil Super Moto 4T 20W-50 combines highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

Features	Advantages and Potential Benefits
Good wear protection	Helps extend engine life
Thermal and oxidation stability	Helps keep engines clean for smoother operation
Good corrosion protection	Protects critical engine components

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
JASO MA
JASO MA2

Properties and Specifications

Property	
Grade	SAE 20W-50
Sulfur, mass%, ASTM D2622	0.52
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	5.2
Viscosity Index, ASTM D2270	130
Cold-Cranking Simulator, Apparent Viscosity @ -10 C, mPa.s, ASTM D5293	3500
Foam, Sequence I, Stability, no Option A, ml, ASTM D892	0
Foam, Sequence I, Tendency, no Option A, ml, ASTM D892	0

Property	
Flash Point, °C, ASTM D92	230
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	20.5
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	5.5
Noack Volatility, mass%, ASTM D5800	9

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022
Mobil Oil Nigeria PLC
Lekki Peninsula Road, Victoria Island, Lagos, Nigeria

+ 234 1 545 1696
<http://exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved