



## Mobil Super™ 2000 5W-30

Mobil Passenger Vehicle Lube , Nigeria

### Product Description

Mobil Super 2000 5W-30 is an enhanced-premium semi-synthetic motor oil meeting the latest industry engine oil specifications. It is designed to provide an excellent level of protection and performance under the most demanding conditions.

### Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 5W-30 contains low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy. Mobil Super 2000 5W-30 helps to promote long engine life.

Mobil Super 2000 5W30:

- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start up
- Excellent high temperature protection thanks to its high quality base oil formulation

### Applications

Mobil Super 2000 5W-30 product is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
Ford WSS-M2C915-A
GM 6094M

<b>This product meets or exceeds the requirements of:</b>
API SN
API SM
Ford WSS-M2C929-A
Ford WSS-M2C946-A

**This product meets or exceeds the requirements of:**

Chrysler MS-6395

API SN Resource Conserving

**Properties and Specifications**

Property	
Grade	SAE 5W-30
Appearance, AMS 1738	Clear and Bright
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.6
Odor, AMS 1695	PASS
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	5730
Pour Point, °C, ASTM D97	-36
Total Base Number, mgKOH/g, ASTM D2896	8.2
Viscosity Index, ASTM D2270	157
Flash Point, Cleveland Open Cup, °C, ASTM D92	227
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	63.6
Mini-Rotary Viscometer, Yield Stress, -35 C, Pa, ASTM D4684	16900
Density @ 15 C, g/ml, ASTM D4052	0.8605

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

Mobil Oil Nigeria PLC

Lekki Peninsula Road, Victoria Island, Lagos, Nigeria

+ 234 1 545 1696

<http://exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved