



Mobil Delvac 1300 Series

Mobil Commercial Vehicle Lube , Nicaragua

High Performance Diesel Engine Oils

Product Description

Mobil Delvac 1310, 1320, 1330, 1340, and 1350 are high performance monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Delvac 1300 monogrades are used in a wide range of applications where a monograde lubricant is recommended.

Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life Less wear Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control Controls formation of acids when using higher sulfur fuels

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- On highway light and heavy duty trucking
- Off highway industries including: construction, mining, quarrying, and agriculture
- Hydraulic system and wet breaks in mobile equipment where a SAE 20 diesel engine oil is required (Delvac 1320)

Specifications and Approvals

Mobil Delvac 1300 are also recommended by ExxonMobil for use in applications requiring:	MOBIL 1320	DELVAC	MOBIL 1330	DELVAC	MOBIL 1340	DELVAC	MOBIL 1350	DELVAC
API CF	X		X		X		X	
API SF	X		X		X		X	
MB 227.0	X							

Properties and Specifications

Property	MOBIL DELVAC 1320	MOBIL DELVAC 1330	MOBIL DELVAC 1340	MOBIL DELVAC 1350
Grade	SAE 20	SAE 30	SAE 40	SAE 50
Ash, Sulfated, mass%, ASTM D874	1.1	1.1	1.1	1.1

Property	MOBIL DELVAC 1320	MOBIL DELVAC 1330	MOBIL DELVAC 1340	MOBIL DELVAC 1350
Density @ 15 C, g/ml, ASTM D4052	0.887	0.89	0.897	0.902
Flash Point, Cleveland Open Cup, °C, ASTM D92	232	256	254	260
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.4	11.8	14.6	19.9
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	61	106	136	232
Pour Point, °C, ASTM D97	-21	-21	-30	-18
Total Base Number, mgKOH/g, ASTM D2896	10	10	10	10
Viscosity Index, ASTM D2270	108	99	99	99

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved