



## MOBIL ALTO KILOMETRAJE 25W60

Mobil Passenger Vehicle Lube , Nicaragua

High Mileage Conventional Engine Oil

### Product Description

Mobil™ Alto Kilometraje is a unique formula that is especially designed for engines with over 100,000 kilometers. The 25W-60 viscosity provides a thick oil film that helps protect gasoline engines that operate in severe service such as high temperatures and in city traffic where stop-and-go driving is common. Mobil Alto Kilometraje is formulated from quality base stocks combined with performance additives, which help protect against the formation of sludge and corrosion.

### Features and Benefits

Mobil Alto Kilometraje:

- Helps to reduce engine wear and corrosion in higher mileage vehicles
- Protects under a wide variety of operating conditions, especially high temperatures
- Helps reduce oil leakage due to the thick oil film
- Reduce oil consumption

### Applications

Mobil Alto Kilometraje is recommended by ExxonMobil for higher mileage vehicles including turbo charged, super charged, fuel injected, multi-valve and normally aspirated engines. Before using Mobil Alto Kilometraje, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

### Specifications and Approvals

**This product meets or exceeds the requirements of:**

API SL

API SJ

### Properties and Specifications

Property	
Grade	SAE 25W-60
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	24.5
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	262
Density @ 15 C, g/ml, ASTM D4052	0.899
Pour Point, °C, ASTM D97	-24
Flash Point, Cleveland Open Cup, °C, ASTM D92	270

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved